

YAPI 100 no C1T

Cement Based, Tile and Ceramic Adhesive

Description

Yapi 100 no is a cement-based, high-stability tile and ceramic adhesive that can be used horizontally indoors and outdoors.

In compliance with TS EN 12004-1:2017 C1 standards.

Ministry of Public Works and Settlement Item No: 04.013/1

C1: Cement Based Normal Hardened Adhesive Fields of Application

- Indoors and outdoors, horizontal applications,
- In all kinds of concrete screed, plaster, screed and cement based surfaces,
- In laying of coating materials such as vitrified tiles.
- It is used in coating materials of maximum 2x4 tile size.

Advantages

- Only mixes with water.
- Easily prepared and applied.
- Has an ideal application time.
- Does not slip in vertical applications.
- Economical.

Technical Data

| | |
|---------------------------------|--|
| Structure of Material | Special Cement, Mineral Filler, Polymer Additive |
| Density | 1,80 kg/lt |
| Color | Gray |
| Bond Strength 28 days | $\geq 0,5 \text{ N/mm}^2$ |
| Application Thickness | Between 3-10 mm |
| Application Surface Temperature | +5°C / +45°C |
| Service Temperature | |
| Initial Curing Time | -25°C / + 70°C 5-10 minutes |
| Working Time | 1 hours |
| Open Waiting Time | 20 minutes |
| Wettability | Min. %90 |
| Grouting Application | 24 hours later |

